

INFRARED HEATERS

Comforting warmth for body and soul


With infrared systems from EOS you will create the perfect basis for powerful, soothing heat.

Thanks to the short heat-up times, the beneficial in the treatment of pain.

against accidental contact.

With the perfectly matched control units from EOS with numerous additional functions, the infrared experience becomes an even greater pleasure and leaves nothing to be desired.

	IR-A	IR-B	IR-C
Radiation	Short wave radiation	Medium wave radiation	Long wave radiation
Skin depth	Sub-skin Subcutis	Upper skin Dermis/Epidermis	Upper skin Epidermis
Effect	Deeper impact	Warming of the upper skin	Warming of the upper skin
	IR-C IR-B	IR-A Corneous	laver



















EOS IRS 30 Ceramic

tor shield of polished aluminium.

tion in the area of the calves.

Dimensions HWD: 560 x 185 x 65 mm

IR heater for sauna- and IR warming cabins

With 300 W ceramic emitter, long-wave IR-C range. Reflec-

With protective flocked safety grill (black). Completely as-

Recommended e. g. as calf heater, for horizontal installa-

sembled with 3 m silicone coated cable 3 x 1.5 mm².



















Affordable entry-level model with 350 W, 400 W or 500 W,

With protective flocked safety grill (black). Completely as-

sembled with 3 m silicone coated cable 3 x 1.5 mm².

Dimensions HWD: 560 x 185 x 65 mm (EOS IRS 40)

Dimensions HWD: 900 x 185 x 65 mm (EOS IRS 35/50)

EOS IRS 35 | IRS 40 RHK | IRS 50 RHK

IR heater for sauna- and IR cabins

long-wave IR-C range.





















high-quality IR heaters are very quickly ready for operation, as it does not heat the surroundings, but the body itself. IR heat has been proven to have a positive effect on health the gentle heat relieves tension and can be

IR heaters from EOS let you experience a pleasant feeling of well-being and ensure a varied wellness experience. All EOS IR heaters are equipped with a specially flocked protective grille and thus offer optimal protection

o-skin ocutis	Upper skin Dermis/Epidermis	Upper skin Epidermis	Dimensions AWD: 883 x 200 x 60 mm	
	Warming of the upper skin	Warming of the upper skin	Model (with / without protective grill)	
			EOS Vitae Protect Compact (350 W)	94
R	-A Corneous	lavor	EOS Vitae Protect Compact (500 W)	94
	Germ		EOS Vitae Protect Compact (750 W)	94
	Upp	per skin	EOS Vitae Protect+ Compact (350 W)	94
>	— Scle	era	EOS Vitae Protect+ Compact (500 W)	94
_			FOS Vitae Protect+ Compact (750 W)	94

EOS Vitae Protect Compact series

IR heater for sauna- and IR warming cabins

EOS Vitae Protect Compact: incl. special ceramic glass filter for additional dispersion of the infrared heat and humidity protection. Available with or without protective flocked safety grill (black).

Vertical Installation IR A IR B IR C IR C

VITAE guartz-glass emitter with 350, 500, 750 W. The versions 500 W and 750 W feature a built-in inrush current limiter. Full-spectre range – IR-A, IR-B und IR-C, full power output in less than 1 sec. With pre-assembled housing with reflector shield and protective flocked safety grill (black). With 3 m silicone coated cable 3 x 1.5 mm²

Dimensions HWD: 795 x 200 x 60 mm

EOS Vitae Protect+ Compact: as Vitae Protect, but with built-in dimmer for quick and easy adjustment of the heating intensity. A separate dimmer is no longer required. Dimensions HWD: 885 x 200 x 60 mm

Model (with / without protective grill)	Item no.
EOS Vitae Protect Compact (350 W)	94 7293 / 94 728
EOS Vitae Protect Compact (500 W)	94 7294 / 94 728
EOS Vitae Protect Compact (750 W)	94 7295 / 94 728
EOS Vitae Protect+ Compact (350 W)	94 7296 / 94 729
EOS Vitae Protect+ Compact (500 W)	94 7297 / 94 729
EOS Vitae Protect+ Compact (750 W)	94 7298 / 94 729



EOS Vitae Compact: VITAE guartz-glass emitter with 350, 500, 750 W. The versions 500 W and 750 W feature a builtin inrush current limiter. Full-spectre range – IR-A, IR-B und IR-C, full power output in less than 1 sec.

With pre-assembled housing with reflector shield and protective flocked safety grill (black). With 3 m silicone coated cable 3 x 1.5 mm².

Dimensions HWD: 745 x 185 x 65 mm

Dimensions HWD: 815 x 185 x 65 mm

EOS Vitae+ Compact: as Vitae, but with built-in dimmer for quick and easy adjustment of the heating intensity. A separate dimmer is no longer required. Not suitable for horizontal installation and for installation in the cabin ceiling – risk of fire due to due to heat congestion!

Model (with protective grill)	Item no.
EOS Vitae Compact (350 W)	94 6502
EOS Vitae Compact (500 W)	94 5450
EOS Vitae Compact (750 W)	94 5451
EOS Vitae+ Compact (350 W)	94 6997
EOS Vitae+ Compact (500 W)	94 6998
EOS Vitae+ Compact (750 W)	94 6999

Model Item no. EOS IRS 30 (300 W) 94 1878

Model	Item no.
EOS IRS 35 (350 W)	94 4305
EOS IRS 50 (500 W)	94 4306
EOS IRS 40 (400 W)	94 4012

EOS IR-Heating foils

IRF 650 W 1700 x 800 mm

IRF 550 W 1450 x 800 mm

IRF 450 W 1600 x 600 mm

IRF 350 W 1250 x 600 mm 1170 x 520 mm

600 x 300 mm 520 x 220 mm

1600 x 400 mm

Heating foils for salt caves, IR- and warming cabins

For concealed installation e. g. behind wooden panelling. Flat and highly flexible. Recommended inner wall thickness up to max. 12 mm. Long-wave IR-C range.

With automatic on-surface thermostatic limiter 100 °C. Working temperature approx. 90 – 100 °C.

Available in various sizes and power outputs.

For technical reasons, the effective output can deviate from the nominal value by up to +5%/-10%.

Surface (H xW)

1620 x 720 mm

1370 x 720 mm

1520 x 520 mm

1520 x 320 mm

94 3742

94 3743

94 3744

94 3745

94 3835

94 3891

EOS InfraSteam

Compact slim-size vaporizer for IR-warming cabins.

With built-in control unit. Very slim, space-saving design Manual water tank filling through the removable essence bowl. Integrated dry-run protection with acoustic low water alarm. Water tank with approx 1.5 l volume

With pre-mounted 3 m mains cord.

Dimmer

For use in the cabin. Especially suitable for Vitae quartz glass heater for a quick adjustment of the heating intensitv. Maximum load up to 1 kW.

Top cover

Practical cover panel for corner installation of IR heaters. With protective flocked surface coating (black). One

Model	Item no.
OS InfraSteam	94 4140A
Dimmer	94 7467
op cover for EOS IRS / Vitae series	94 4566
op cover for EOS Vitae Protect series	94 6596





EOS InfraTec Classic

For IR-cabins

Illuminated LCD-Display (time, functions, errormessages). Temperature control range 30 °C to 70 °C. Variable heating time 1 to 99 minutes. Switch for cabin light.

Integrated main on/off switch. Flush-mounting installation.

Includes temperature sensor with 3 m cable.

Power supply: 230 V N ~ 50 Hz Switching capacity: 3500 W



EOS InfraTec Premium

For IR-cabins (dimmable and switchable)

Compact size flush-mounting display panel and a separate relay box. Illuminated LCD-Display (time, functions, error messages), multi-language menu navigation.

Temperature control range 30 to 70 °C. With the optional temperature sensor for heating foils control, regulation can be carried out either as per air temperature or heat intensity.

The control unit has three outputs (2 x 1500 W dimmable, 500 W switchable) and cabin light control (230 V output).

Includes temperature sensor with 5 m cable.

Power supply: $230 \text{ V N} \sim 50 \text{ Hz}$ Switching capacity: 3500 W



EOS EmoTec IR

For IR-cabins (dimmable and switchable)

Premium class digital control unit for demanding private and commercial operation.

Very large scope of functions and features. Additional extension modules for music and colour light control are optionally available.

Temperature control range 30 to 70 °C. Heating control as per air temperature or heat intensity.

Three separate outputs: two are dimmable, one is switchable – so you can create individual zones or heating groups (e.g. back, front, side, etc.).

Supports all types or IR emitters and heating foils. Total power output can be increased to 10.5 kW with extension modules SBM-IR.

Includes temperature sensor with 5 m cable.



EOS InfraStyle | InfraStyle i

For IR-cabins (dimmable and switchable)

Luxury class digital control unit for demanding private and commercial IR-cabins.

Luxurious display panel with glass front and capacitive buttons. Available in black or white design. Functions and features as EOS EmoTec IR model.

Includes temperature sensor with 5 m cable.

EOS InfraStyle i: Luxury class digital control unit with display panel suitable for installations **inside** the IR-cabin.

Exclusive display panel design with glass front and stylish wooden inlay of maple or walnut with integrated capacitive button for quick and easy operation.

Model	Item no.
EOS InfraTec Classic – without cable set	94 4388
EOS InfraTec Classic – with cable set	94 4334

Model	Item no.
EOS InfraTec Premium	94 7808

Model	Item no.
EOS EmoTec IR Anthrazit / Silber	94 7044
EOS EmoTec IR Weiß / Silber	94 7045

Model	Item no. black/white
EOS InfraStyle	94 7046 / 94 7047
EOS InfraStyle i maple	94 7048 / 94 7049
EOS InfraStyle i walnut	94 7070 / 94 7071

Accessories



SBM-App module

The App module allows to control your cabin remotely from a smart phone or tablet-PC with the "EOS Spa Control" app from any place worldwide (internet access required). For Android and Apple iOS. Delivery does not include a smart phone or a tablet-pc!

Compatible control units: EOS EmoTec-, EmoStyle-, InfraStyle-series, EmoTouch 3-Sauna.



Aroma bowl for infrared heaters

With the aroma bowl, you have the opportunity to bring even more nature and wellness into your cabin. Suitable for the EOS Vitae and Vitae Protect IR heaters with protective grill. Particularly recommended with Himalaya salt rocks.